

FMS® Plus - Forest Motorized System Plus

This completely new motorized track makes it possible to create even longer treatments and will hold 8 lbs/ft. Just as the original Forest Motorized track provides ultra-quiet and smooth operation of your draperies, so does the FMS Plus track. White aluminum extrusion, powder coated. Wall, ceiling or recess mount.



51623-25 white 23' x 10 tracks/bundle =230'

ASSEMBLED SYSTEM includes track, motor, power supply, amd Diamond Sense Remote or Diamond wall switch.

FMS Plus Motors, Power Supplies and Control Options



52925-25 Forest Shuttle HD -59 Black w/ built-in receiver 1/box



52940-2524 v Power Supply
for Eco Shuttle ONLY
7' power cord
1/box



52939-25Forest Shuttle Eco
w/ built-in receiver
1/box



52931-25D white 52931-59D black -59 Black Diamond Sense Remote RF, 15 channel w/ holder Range 98' 1/box



52944-25Forest Shuttle Z-Wave w/ built-in receiver 1/box



52932-25Z-Wave Adaptor
Use with Z-Wave motor
to communicate
with Diamond Remote
1/box



COMING SOON!

52926-25Forest Shuttle iOn
Lithium Ion Battery
1/box



52933-25 white 52933-59 black -59 Black Diamond Wall Switch 2 channel 1/box



52928-25 7' 6" power cord 52934-25 16' power cord 24 v Power Supply for Eco HD & Z-Wave Shuttles 1/box



52943-25 white 52943-59 black -59 Black RF Multi Wall Switch 16 channel LED Screen 1/box NOT PART OF ASSEMBLED SET

FMS Plus Transport Components



9112-25 Transport Belt roll of 328 ft.



53903-25 Motor Pulley Connects motor to track 1/box



53910-25 Return Pulley 1/box



53911-25 Upside Down Pulley 1/box



53912-25 Coverplate for Recess Motor and Return Pulley 1/box



53913-25 Coverplate for Recess, Upside Down, and Return Pulley 1/box



FMS Plus Carriers



52008-25Slim Line Klick Carrier Draperies hang to conceal track box of 250



52004-25 Low Profile Ball Bearing Carrier box of 1000



52009-25Ball Bearing Carrier for motorization box of 250



2111-25 80% fullness, 2 3/8" OC 2112-25 100% fullness, 2 1/8" OC 2115-25 120% fullness, 1 7/8" OC Two-Piece Connected Snap Carrier w/ Square Base In plastic sleeve. Use 4 1/4" snap tape. roll of 500

2114-25 60% fullness, 2 5/8" OC

FMS Plus Master



53908-25 Overlap Right FMS Plus Master Carrier box of 10



53909-25 Underlap Left FMS Plus Master Carrier Assembly required box of 10

FMS Plus Brackets



3003-25 HD Ceiling Bracket w/ Smart Klick box of 100



NEW!

30031-25 -59 Black Ceiling Bracket Cover box of 100



53202-253" Smart Klick Wall Bracket w/ wide base adjusts 3"-4 1/2" box of 100



53206-25 6" Smart Klick Double Wall Bracket w/ wide base adjusts 2 1/2"-4" & 6"-7.5" box of 50



3800-25MTS Wall Bracket
To install the track
inside a frame
box of 20



3006-25 Suspension Bracket Tube 39" extension 10/box



3007-25Suspension Bracket
Insert Screw
box of 100



3008-25 Suspension Bracket Top box of 25



3009-25Suspension Bracket
Klick System Clip
box of 50



51723-25 Recess Profile, 23'



51724-25 Recess Profile Fixing Strip, 23'



53914-25Recess Profile Wedge box of 10

Forest Shuttle Family of Motors

Touch Impulse Technology opens or closes drapes with a gentle pull. Integrated emergency control insures manual operation of the drapery in case of power failure. Capable of integrating with all major home automation systems, the Forest Shuttle is offered in 3 versions which address various communication protocols. Shuttles HD and Eco integrate with your smart home technology via dry contacts and RS485 protocol for use with popular automation systems including Lutron, Control 4, Crestron, Somfy, and many others. The Z-Wave Shuttle offers app control through Samsung's SmartThing and Amazon's Alexa devices. Or, use Z-wave's mesh network to integrate via dry contacts.



All Forest Shuttle Motors include a 10-Year Warranty - the only one on the market.



Comparison Chart

| | Forest | Forest |
|------------------------------|--|---|
| | Shuttle HD (M) | Shuttle Eco (S) |
| DIMENSIONS | Motor: 2.76" x 1.97" x 9.5" / Receiver Internal | Motor: 2.76" x 1.97" x 7.5" / Receiver Internal |
| MOUNTING | Wall or Ceiling; Can be spliced | Wall or Ceiling; Can be spliced |
| MAXIMUM WEIGHT | 160 lbs per motor / 120 lbs per motor - curved track | |
| TRAVEL SPEED | 5.5" per second standard / 7" per sec maximum | |
| RECEIVER | Internal | Internal |
| AMPERAGE | .6 amps / 70 watts / 110 volt plug-n-play | .35 amps / 40 watts / 110 volt plug-n-play |
| TORQUE | 1.5 Nm | 1.0 Nm |
| NOISE LEVEL | < 40 dB(A) | < 40 dB(A) |
| TOUCH IMPULSE TECHNOLOGY | V | \checkmark |
| EMERGENCY CONTROL | ✓ | ✓ |
| RF COMMUNICATION STANDARD | √ | √ |
| Z-WAVE COMMUNICTION | | |
| AUTOMATION SYSTEM COMPATIBLE | RS485 & dry contacts ✓ | RS485 & dry contacts ✓ |
| WARRANTY | 10 Year | 10 Year |





| Forest | Forest | |
|---|--|--|
| Shuttle iOn | Shuttle Z-Wave | |
| Motor: 2" x 3" x 12.25" / Receiver Internal | Motor: 2.76" x 1.97" x 9.5" / Receiver Internal | |
| Wall or Ceiling; Can be spliced | Wall or Ceiling; Can be spliced | |
| 55 lbs per motor / 40 lbs per motor - curved track | 160 lbs per motor / 120 lbs per motor - curved track | |
| 5.5" per second standard | 5.5" per second standard / 7" per sec maximum | |
| Internal | Internal | |
| Lithium Ion Battery + charger (3-4months between charges) | .6 amps / 70 watts / 110 volt plug-n-play | |
| 1 Nm | 1.5 Nm | |
| < 40 dB(A) | < 40 dB(A) | |
| J | ✓ | |
| ✓ | √ | |
| ✓ | dry contacts ✓ | |
| | ✓ | |
| RS485 & dry contacts ✓ | dry contacts ✓ | |
| 10 years on motor. 2 years on battery pack. | 10 Year | |
| | | |